



Software Development Kit

BCR

Copyright 2020

Recogniform Technologies SpA

HOW TO CONTACT US

Recogniform Technologies SpA

Contrada Concistocchi

87036 Rende (CS), Italy

Phone : +39 0984 404174

Fax : +39 0984 830299

Internet : www.recogniform.com

E-Mail : info@recogniform.com

Table of contents

Introduction	6
Copyright	6
License	6
Overview	6
Usage	10
Visual C++	10
C#	10
Visual Basic	10
Visual Basic .NET	10
Delphi	10
Java	10
API References	12
BCR_Init	12
BCR_Done	13
BCR_Recognize	14
BCR_RecognizeArea	15
BCR_RecognizeEx	18
BCR_GetCodesCount	20
BCR_GetCodeLen	21
BCR_GetCodeText	22
BCR_GetCodeArea	24
BCR_GetCodeCheck	25
BCR_GetCodeType	26
BCR_GetCodeOrientation	27
BCR_LoadImage	29
BCR_ImportDDB	30
BCR_FreeImage	31
LoadBCRLibrary	32
FreeBCRLibrary	32
Sample	36
Samples	36

Visual C++.....	36
Visual Basic.....	37
Delphi	38

Introduction

I

1 Introduction

1.1 Copyright

The software and the documentation are property of:

Recogniform Technologies SpA
Contrada Concistocchi
87036 Rende (CS)
Italy
www.recogniform.com
info@recogniform.com

1.2 License

It is illegal to copy or reproduce this manual, or any part thereof, in any shape or form.

The information contained in this manual is subject to change without notice and does not present a commitment on the part of Recogniform Technologies SpA.

Recogniform Technologies SpA shall not be held liable for technical or editorial errors and/or omissions made here, nor for incidental or consequential damages resulting from the furnishing, performance, or use of the software and documentation.

Recogniform Technologies SpA reserves the right to make changes to the software and documentation without notice.

Product names mentioned here are used for identification purposes only and may be tradenames and/or registered trademarks of their respective companies.

YOU CANNOT DISTRIBUTE SOFTWARE INCLUDING THIS SDK LIBRARY UNLESS YOU HAVE A WRITTEN AGREEMENT (ROYALTIES FREE OR ROYALTIES BASED) WITH RECOGNIFORM TECHNOLOGIES SPA

1.3 Overview

The Recogniform Barcode Recognition Library 5.0 allows to recognize barcodes from images acquired using a scanner.

The barcodes type recognizable are:

- 2of5Interlaved

- 2of5IATA
- 2of5Industrial
- 2of5Matrix
- 2of5DataLogic
- Code39
- PharmaCode
- EAN13
- EAN8
- UPCA
- UPCE
- EXT2
- EXT5
- CodaBar
- MSI
- Code11
- Code128
- Code93
- Code39Extended

The barcodes can be recognized in any orthogonal orientation:

- LeftToRight
- RightToLeft
- TopToBottom
- BottomToTop.

The recognition process is fast and accurate and for each recognized barcode you can get:

- length
- data
- area
- orientation
- checksum flag

We can also create specialized and customized recognizers for specific use if you need.

Usage



2 Usage

2.1 Visual C++

You have to include the RECOBCRAPI.C in your program.

Before to execute your application make sure the *RECOBCR.DLL* is available in your same .exe directory or in windows\system directory.

2.2 C#

You have to include the RECOBCRAPI.CS in your program.

Before to execute your application make sure the *RECOBCR.DLL* is available in your same .exe directory or in windows\system directory.

2.3 Visual Basic

You have to include the RECOBCRAPI.BAS in your program.

Before to execute your application make sure the *RECOBCR.DLL* is available in your same .exe directory or in windows\system directory.

2.4 Visual Basic .NET

You have to include the RECOBCRAPI.VB in your program.

Before to execute your application make sure the *RECOBCR.DLL* is available in your same .exe directory or in windows\system directory.

2.5 Delphi

You have to include the RECOBCRAPI.PAS in your program.

Before to execute your application make sure the *RECOBCR.DLL* is available in your same .exe directory or in windows\system directory.

2.6 Java

You have to use 32 bit JVM and you have to include the RECOBCRAPI.JAVA in your program. Before to execute your application make sure the *RECOBCR.DLL* is available in your same .jar directory.

API References



3 API References

3.1 BCR_Init

C/C++ Declaration

```
__stdcall long BCR_Init(char* Name, char* Key);
```

C# Declaration

```
int BCR_Init(string Name, string Key);
```

Visual Basic Declaration

```
Function BCR_Init(ByVal Name As String, ByVal Key  
As String) As Integer
```

Visual Basic .NET Declaration

```
Function BCR_Init(ByVal Name As String, ByVal Key  
As String) As Integer
```

Delphi Declaration

```
function BCR_Init(Company:PAnsiChar;  
LicenseKey:PAnsiChar):Integer; stdcall;
```

Java Declaration

```
int BCR_Init(String Name, String Key);
```

Description

This is the first function to call: initialize the library and returns a session handle to use in next calls. When you buy the library you receive an "user" and a "password" string necessary to initialize the library in normal mode: without this value or with wrong values the library is initialized in evaluation mode. The evaluation mode works exactly as normal mode but some time, when you call the recognition function, is displayed a warning dialog box remembering the evaluation state: you can close it and continue to work with no problems.

Parameters

User (in) - then user name string

Password (in) - then password string

Return values

The session handle if the library is initialized, 0 otherwise.

Note

You should use BCR_Init at application startup and BCR_Done at application closing and not every time you need to recognize an image.

The “status” string, shown in the windows dialog, is built by 1 and 0 meaning OK or KO for this checking in the order from left to right:

- SDK initialized with valid user/key
- License file integrity
- License file matching sdk version
- Computer verification done or not required
- Dongle verification done or not required
- Date expiration done or not required
- SDK option used unlocked

3.2 BCR_Done

C/C++ Declaration

```
__stdcall void BCR_Done(long Session);
```

C# Declaration

```
void BCR_Done(int Session);
```

Visual Basic Declaration

```
Sub BCR_Done(ByVal Session As Integer)
```

Visual Basic .NET Declaration

```
Sub BCR_Done(ByVal Session As Integer)
```

Delphi Declaration

```
procedure BCR_Done(SessionHandle:Integer);
stdcall;
```

Java Declaration

```
void BCR_Done(int SessionHandle);
```

Description

This is the last function to call when you don't need more services from the library: de-initialize the library and free all used resources.

Parameters

SessionHandle (in) - the session handle to free

Return values

n/a

Note

You should use BCR_Init at application startup and BCR_Done at application closing and not every time you need to recognize an image.

3.3 BCR_Recognize

C/C++ Declaration

```
__stdcall long BCR_Recognize(long SessionHandle,
long DIBIn, long CodeType, long ExpectedCodes,
long MinCodeLen, long MaxCodeLen, long
VirtualLaserSize, long VirtualLaserStep);
```

C# Declaration

```
int BCR_Recognize(int SessionHandle, int DIBIn,
int CodeType, int ExpectedCodes, int MinCodeLen,
int MaxCodeLen, int VirtualLaserSize, int
VirtualLaserStep);
```

Visual Basic Declaration

```
Function BCR_Recognize(Byval SessionHandle As
integer, Byval DIBIn As integer, Byval CodeType As
integer, Byval ExpectedCodes As integer, Byval
MinCodeLen As integer, Byval MaxCodeLen As
integer, Byval VirtualLaserSize As integer, Byval
```

```
VirtualLaserStep As integer) As integer
```

Visual Basic .NET Declaration

```
Function BCR_Recognize(Byval SessionHandle As
integer, Byval DIBIn As integer, Byval CodeType As
integer, Byval ExpectedCodes As integer, Byval
MinCodeLen As integer, Byval MaxCodeLen As
integer, Byval VirtualLaserSize As integer, Byval
VirtualLaserStep As integer) As integer
```

Delphi Declaration

```
Function BCR_Recognize(SessionHandle, DIBIn,
CodeType, ExpectedCodes, MinCodeLen, MaxCodeLen,
VirtualLaserSize, VirtualLaserStep):Integer;
stdcall;
```

Java Declaration

```
int BCR_Recognize(int SessionHandle,int DIBIn, int
CodeType, int ExpectedCodes,int MinCodeLen, int
MaxCodeLen, int VirtualLaserSize, int
VirtualLaserStep);
```

Note

See BCR_RecognizeEx

This function is available only for compatibility with old version.

3.4

BCR_RecognizeArea

C/C++ Declaration

```
long BCR_RecognizeArea(long Session, long
DIBHandle, long Left, long Top, long Right, long
Bottom, long CodeType, long MaxCodes, long MinLen,
long MaxLen, long LaserSize , long LaserStep, long
Quality, long Orientation, long VerifyCheckDigit);
```

C# Declaration

```
int BCR_RecognizeArea(int Session, int DIBHandle,
int Left, int Top, int Right, int Bottom, int
CodeType, int MaxCodes, int MinLen, int MaxLen,
int LaserSize , int LaserStep, int Quality, int
```

```
Orientation, int VerifyCheckDigit);
```

Visual Basic Declaration

```
Function BCR_RecognizeArea(ByVal Session As Integer, ByVal DIBHandle As Integer, ByVal Left As Integer, ByVal Top As Integer, ByVal Right As Integer, ByVal Bottom As Integer, ByVal CodeType As Integer, ByVal MaxCodes As Integer, ByVal MinLen As Integer, ByVal MaxLen As Integer, ByVal LaserSize As Integer, ByVal LaserStep As Integer, ByVal Quality As Integer, ByVal Orientation As Integer, ByVal VerifyCheckDigit As Integer) As Integer
```

Visual Basic .NET Declaration

```
Function BCR_RecognizeArea(ByVal Session As Integer, ByVal DIBHandle As Integer, ByVal Left As Integer, ByVal Top As Integer, ByVal Right As Integer, ByVal Bottom As Integer, ByVal CodeType As Integer, ByVal MaxCodes As Integer, ByVal MinLen As Integer, ByVal MaxLen As Integer, ByVal LaserSize As Integer, ByVal LaserStep As Integer, ByVal Quality As Integer, ByVal Orientation As Integer, ByVal VerifyCheckDigit As Integer) As Integer
```

Delphi Declaration

```
function BCR_RecognizeArea(Session, DIBHandle, Left, Top, Right, Bottom, CodeType, MaxCodes, MinLen, MaxLen, LaserSize, LaserStep, Quality, Orientation, VerifyCheckDigit):Integer; stdcall;
```

Java Declaration

```
int BCR_RecognizeArea(int Session, int DIBHandle, int Left, int Top, int Right, int Bottom, int CodeType, int MaxCodes, int MinLen, int MaxLen, int LaserSize, int LaserStep, int Quality, int Orientation, int VerifyCheckDigit);
```

Description

This is the function performing the recognition of the barcode in a defined area: you have to call this function after library initialization to perform the barcode recognition. The DIB handle can contain a single barcodes or multiple barcodes.

Parameters

SessionHandle (in) - the session handle to use

DIBIn (in) - the handle of the monochrome DIB to recognize

Left (in) - the left barcode coordinates

Top (in) - the top barcode coordinates

Right (in) - the right barcode coordinates

Bottom (in) - the bottom barcode coordinates

CodeType (in) - the types of barcodes to recognize: can be a combination (or) from 1 = 2of5Interlaved, 2=2of5IATA, 4=2of5Industrial, 8=2of5Matrix, 16=2of5DataLogic, 32=Code39, 64=PharmaCode, 128=EAN13, 256=EAN8, 512=UPCA, 1024=UPCE, 2048=EXT2, 4096=EXT5, 8192=CodaBar, 16384=MSI, 32768=Code11, 65536=Code128, 131072=Code93, 262144=Code39Extended

MaxCodes (in) - the maximum number of expected barcodes: the system stop to search more codes if this number of codes is recognized

MinLen (in) - the minimum length in characters (including start/stop characters and check digit) expected for a barcode.

MaxLen (in) - the maximum length in characters (including start/stop characters and check digit) expected for a barcode.

LaserSize(in) - the height of virtual laser used to scan the image. The system will process together a number of contiguous rows equal to this value. Use 3 as default.

LaserStep(in) - the step of virtual laser used to scan the image. The system will skip between consecutive scans a number of rows equal to this value. Use 32 as default.

Quality(in) - the quality expected for the processing image: can be 1 = Normal, 2=Dark, 3=Light

Orientation(in) - the expected orientation of barcodes: can be a combination (or) from 1 = LeftToRight, 2=RightToLeft, 3=TopToBottom, 4=BottomToTop

VerifyCheckDigit (in) - the flag allowing to enable (1) or disable (0) the verification of barcode check digit. When disabled, if the barcode has a check digit, it will be returned with the barcode data.

Return values

The number of barcodes recognized if success, 0 otherwise.

Notes

The library works with standard DIBs images. Refer to Microsoft documentation for additional info about Device Indipendent Bitmaps. The barcode recognition is executed on b&w images, so if you use a grayscale or color image the library automatically binarize it before to perform processing. You could also consider to use our *Dynamic Thresholding Library* to get better result in conversion.

3.5 BCR_RecognizeEx

C/C++ Declaration

```
__stdcall long BCR_RecognizeEx(long SessionHandle,
long DIBIn, long CodeType, long ExpectedCodes,
long MinCodeLen, long MaxCodeLen, long
VirtualLaserSize, long VirtualLaserStep, long
ImageQuality, long Orientation, long
CheckDigitVerification);
```

C# Declaration

```
int BCR_RecognizeEx(int SessionHandle, int DIBIn,
int CodeType, int ExpectedCodes, int MinCodeLen,
int MaxCodeLen, int VirtualLaserSize, int
VirtualLaserStep, int ImageQuality, int
Orientation, int CheckDigitVerification);
```

Visual Basic Declaration

```
Function BCR_RecognizeEx(Byval SessionHandle As
Integer, Byval DIBIn As Integer, Byval CodeType As
Integer, Byval ExpectedCodes As Integer, Byval
MinCodeLen As Integer, Byval MaxCodeLen As
Integer, Byval VirtualLaserSize As Integer, Byval
VirtualLaserStep As Integer, Byval ImageQuality As
Integer, Byval Orientation As Integer, Byval
CheckDigitVerification)As Integer
```

Visual Basic .NET Declaration

```
Function BCR_RecognizeEx(Byval SessionHandle As
Integer, Byval DIBIn As Integer, Byval CodeType As
Integer, Byval ExpectedCodes As Integer, Byval
MinCodeLen As Integer, Byval MaxCodeLen As
```

```
Integer, Byval VirtualLaserSize As Integer, Byval
VirtualLaserStep As Integer, Byval ImageQuality As
Integer, Byval Orientation As Integer, Byval
CheckDigitVerification)As Integer
```

Delphi Declaration

```
function BCR_RecognizeEx(SessionHandle, DIBIn,
CodeType, ExpectedCodes, MinCodeLen, MaxCodeLen,
VirtualLaserSize, VirtualLaserStep, ImageQuality,
Orientation, CheckDigitVerification):Integer;
stdcall;
```

Java Declaration

```
int BCR_RecognizeEx(int SessionHandle,int DIBIn,
int CodeType, int ExpectedCodes,int MinCodeLen,
int MaxCodeLen, int VirtualLaserSize, int
VirtualLaserStep, int ImageQuality, int
Orientation, int CheckDigitVerification);
```

Description

This is the function performing the recognition: you have to call this function after library initialization to perform the barcode recognition. The DIB handle can contain a single barcodes or multiple barcodes.

Parameters

SessionHandle (in) - the session handle to use

DIBIn (in) - the handle of the monochrome DIB to recognize

CodeType (in) - the types of barcodes to recognize: can be a combinantion (or) from 1 =2of5Interlaved, 2=2of5IATA, 4=2of5Industrial, 8=2of5Matrix, 16=2of5DataLogic, 32=Code39, 64=PharmaCode, 128=EAN13, 256=EAN8, 512=UPCA, 1024=UPCE, 2048=EXT2, 4096=EXT5, 8192=CodaBar, 16384=MSI, 32768=Code11, 65536=Code128, 131072=Code93, 262144=Code39Extended

ExpectedCodes (in) - the maximum number of expected barcodes: the system stop to search more codes if this number of codes is recognized

MinCodeLen (in) - the minumum length in characters (including start/stop characters and check digit) expected for a barcode.

MaxCodeLen (in) - the maximum length in characters (including start/stop characters and check digit) expected for a barcode.

VirtualLaserSize(in) - the height of virtual laser used to scan the

image. The system will process together a number of contiguous rows equal to this value. Use 3 as default.

VirtualLaserStep(in) - the step of virtual laser used to scan the image. The system will skip between two consecutive scans a number of rows equal to this value. Use 32 as default.

ImageQuality(in) - the quality expected for the processing image: can be 1 = Normal, 2=Dark, 3=Light

Orientation(in) - the expected orientation of barcodes: can be a combination (or) from 1 = LeftToRight, 2=RightToLeft, 3=TopToBottom, 4=BottomToTop

CheckDigitVerification (in) - the flag allowing to enable (1) or disable (0) the verification of barcode check digit. When disabled, if the barcode has a check digit, it will be returned with the barcode data.

Return values

The number of barcodes recognized if success, 0 otherwise.

Notes

The library works with standard DIBs images. Refer to Microsoft documentation for additional info about Device Independent Bitmaps. The barcode recognition is executed on b&w images, so if you use a grayscale or color image the library automatically binarize it before to perform processing. You could also consider to use our *Dynamic Thresholding Library* to get better result in conversion.

3.6 BCR_GetCodesCount

C/C++ Declaration

```
__stdcall long BCR_GetCodesCount(long  
SessionHandle);
```

C# Declaration

```
int BCR_GetCodesCount(int SessionHandle);
```

Visual Basic Declaration

```
Function BCR_GetCodesCount(ByVal SessionHandle As  
Integer)As Integer;
```

Visual Basic .NET Declaration

```
Function BCR_GetCodesCount(ByVal SessionHandle As  
Integer)As Integer;
```

Delphi Declaration

```
Function  
BCR_GetCodesCount(SessionHandle:Integer):Integer;  
stdcall;
```

Java Declaration

```
int BCR_GetCodesCount(int SessionHandle);
```

Description

This is the function to call after the recognition process to get the number of codes recognized in the image.

Parameters

SessionHandle (in) - the session handle to use

Return values

The numbers of recognized codes

3.7 BCR_GetCodeLen

C/C++ Declaration

```
__stdcall long BCR_GetCodeLen(long SessionHandle,  
long CodeIndex);
```

C# Declaration

```
int BCR_GetCodeLen(int SessionHandle, int  
CodeIndex);
```

Visual Basic Declaration

```
Function BCR_GetCodeLen(Byval SessionHandle As  
Integer, Byval CodeIndex As Integer)As Integer;
```

Visual Basic .NET Declaration

```
Function BCR_GetCodeLen(Byval SessionHandle As Integer, Byval CodeIndex As Integer)As Integer;
```

Delphi Declaration

```
Function BCR_GetCodeLen(SessionHandle:Integer, CodeIndex:Integer):Integer;stdcall;
```

Java Declaration

```
int BCR_GetCodeLen(int SessionHandle,int CodeIndex);
```

Description

Retrieves the ASCII text length of one of the codes recognized.

Parameters

SessionHandle (in) - the session handle to use

CodeIndex (in) - the index of the code . First code recognized is 0, last is the BCR_GetCodesCount-1.

Return values

The length of code text.

3.8 BCR_GetCodeText

C/C++ Declaration

```
__stdcall long BCR_GetCodeText(long SessionHandle, long CodeIndex, char *CharBuffer);
```

C# Declaration

```
int BCR_GetCodeText(int Session, int CodeIndex, Buffer As String)
```

Visual Basic Declaration

```
Function BCR_GetCodeText(ByVal Session As Integer, ByVal CodeIndex As Integer, ByVal Buffer As String) As Integer
```

Visual Basic .NET Declaration

```
Function BCR_GetCodeText(ByVal Session As Integer,  
ByVal CodeIndex As Integer, ByVal Buffer As  
String) As Integer
```

Delphi Declaration

```
function  
BCR_GetCodeText(SessionHandle: Integer; ResultIndex:  
Integer; Buffer: PChar): Integer; stdcall;
```

Java Declaration

```
int BCR_GetCodeText(int SessionHandle, int  
CodeIndex, Memory CharBuffer);
```

Description

This is the function to call after the recognition process to get the data recognized.

Parameters

SessionHandle (in) - the session handle to use

CodeIndex (in) - the index of the code . First code recognized is 0, last is the BCR_CodesCount-1.

CharBuffer (out) - the buffer where will be moved the characters recognized. You have to allocate enough space.

Return values

The number of characters moved in the buffer.

Notes

The library works with standard DIBs images. Refer to Microsoft documentation for additional info about Device Indipendent Bitmaps. If you have to recognize a gray-scale image, please consider to use our *Dynamic Thresholding Library* to get better result in conversion.

3.9 BCR_GetCodeArea

C/C++ Declaration

```
__stdcall void BCR_GetCodeRect(long SessionHandle,
long CodeIndex, long *Left, long *Top, long
*Right, long *Bottom);
```

C# Declaration

```
void BCR_GetCodeRect(int SessionHandle, int
CodeIndex, int *Left, int *Top, int *Right, int
*Bottom);
```

Visual Basic Declaration

```
Sub BCR_GetCodeRect (ByVal Session As Integer,
ByVal CodeIndex As Integer, ByRef Left As Integer,
ByRef Top As Integer, ByRef right As Integer,
ByRef bottom As Integer)
```

Visual Basic .NET Declaration

```
Sub BCR_GetCodeRect (ByVal Session As Integer,
ByVal CodeIndex As Integer, ByRef Left As Integer,
ByRef Top As Integer, ByRef right As Integer,
ByRef bottom As Integer)
```

Delphi Declaration

```
Procedure BCR_GetCodeRect
(Session:Integer,CodeIndex:Integer, var
Left:Integer, var Top:Integer, var right:Integer,
var bottom:Integer);stdcall;
```

Java Declaration

```
void      BCR_GetCodeRect(int      SessionHandle,int
CodeIndex,  int   Left,   int   Top,   int   Right,int
Bottom);
```

Description

Retrieves the rectangle coordinates of one of the codes recognized.

Parameters

SessionHandle (in) - the session handle to use
CodeIndex (in) - the index of the code . First code recognized is 0, last is the BCR_GetCodesCount-1.
Left (out) - the buffer where will be moved the left position of the rectangle containing the barcode.
Top (out) - the buffer where will be moved the top position of the rectangle containing the barcode.
Right (out) - the buffer where will be moved the right position of the rectangle containing the barcode.
Bottom (out) - the buffer where will be moved the bottom position of the rectangle containing the barcode.

Return values

None

3.10 BCR_GetCodeCheck

C/C++ Declaration

```
__stdcall long BCR_GetCodeCheck(long SessionHandle, long CodeIndex);
```

C# Declaration

```
int BCR_GetCodeCheck(int SessionHandle, int CodeIndex);
```

Visual Basic Declaration

```
Function BCR_GetCodeCheck(ByVal SessionHandle As Integer, ByVal CodeIndex As Integer)As Integer;
```

Visual Basic .NET Declaration

```
Function BCR_GetCodeCheck(ByVal SessionHandle As Integer, ByVal CodeIndex As Integer)As Integer;
```

Delphi Declaration

```
Function BCR_GetCodeCheck(SessionHandle:Integer, CodeIndex:Integer):Integer;stdcall;
```

Java Declaration

```
int BCR_GetCodeCheck(int SessionHandle, int  
CodeIndex);
```

Description

Retrieves the status of the check digit present in the barcode.

Parameters

SessionHandle (in) - the session handle to use
CodeIndex (in) - the index of the code . First code recognized is 0, last is the BCR_GetCodesCount-1.

Return values

0 if check digits invalid or was not found, 1 if check digit found and valid.

3.11 BCR_GetCodeType

C/C++ Declaration

```
long BCR_GetCodeType(long SessionHandle, long  
CodeIndex);
```

C# Declaration

```
int BCR_GetCodeType(int Session , int CodeIndex  
) ;
```

Visual Basic Declaration

```
Function BCR_GetCodeType (ByVal Session As Long,  
ByVal CodeIndex As Long) As Long
```

Visual Basic .NET Declaration

```
Function BCR_GetCodeType(ByVal Session As Integer,  
 ByVal CodeIndex As Integer) As Integer
```

Delphi Declaration

```
function  
BCR_GetCodeType(SessionHandle:Integer;ResultIndex:  
Integer):Integer;
```

Java Declaration

```
int BCR_GetCodeType(int SessionHandle, int  
ResultIndex);
```

Description

retrieve the type of recognized barcode

Parameters

SessionHandle (in) - the session handle to use

CodeIndex (in) - the index of the code . First code recognized is 0, last is the BCR_GetCodesCount-1.

Return values

The code type is defined as follow:

1 = BCR_2of5Interlaved
2 = BCR_2of5IATA
4 = BCR_2of5Industrial
8 = BCR_2of5Matrix
16 = BCR_2of5DataLogic
32 = BCR_Code39
64 = BCR_PharmaCode
128 = BCR_EAN13
256 = BCR_EAN8
512 = BCR_UPCA
1024 = BCR_UPCE
2048 = BCR_EXT2
4096 = BCR_EXT5
8192 = BCR_CodaBar
16384 = BCR_MSI
32768 = BCR_Code11
65536 = BCR_Code128
131072 = BCR_Code93
262144 = BCR_Code39Extended

3.12 BCR_GetCodeOrientation

C/C++ Declaration

```
__stdcall long BCR_GetCodeOrientation(long  
SessionHandle, long CodeIndex);
```

C# Declaration

```
int BCR_GetCodeOrientation(int SessionHandle, int  
CodeIndex);
```

Visual Basic Declaration

```
Function BCR_GetCodeOrientation(ByVal  
SessionHandle As Integer, ByVal CodeIndex As  
Integer)As Integer;
```

Visual Basic .NET Declaration

```
Function BCR_GetCodeOrientation(ByVal  
SessionHandle As Integer, ByVal CodeIndex As  
Integer)As Integer;
```

Delphi Declaration

```
Function  
BCR_GetCodeOrientation(SessionHandle:Integer,  
CodeIndex:Integer):Integer;stdcall
```

Java Declaration

```
int BCR_GetCodeOrientation(int SessionHandle, int  
CodeIndex);
```

Description

Retrieves the orientation of the recognized barcode.

Parameters

SessionHandle (in) - the session handle to use
CodeIndex (in) - the index of the code . First code recognized is 0, last is the BCR_GetCodesCount-1.

Return values

1 if code is oriented LeftToRight, 2 if oriented RightToLeft, 4 if oriented TopToBottom, 8 if oriented BottomToTop.

3.13 BCR_LoadImage

C/C++ Declaration

```
__stdcall long BCR_LoadImage(long SessionHandle,
char* FileName);
```

C# Declaration

```
int BCR_LoadImage(int SessionHandle, string
FileName);
```

Visual Basic Declaration

```
Function BCR_LoadImage(ByVal Session As Integer,
ByVal FileName As String) As Integer
```

Visual Basic .NET Declaration

```
Function BCR_LoadImage(ByVal Session As Integer,
ByVal FileName As String) As Integer
```

Delphi Declaration

```
Function BCR_LoadImage(Session:Integer,
FileName:PAnsiChar):Integer;stdcall;
```

Java Declaration

```
int BCR_LoadImage(int SessionHandle, String
FileName);
```

Description

This function allows to load an image from file obtaining a DIB handle. Supported files formats are TIF, JPG, PNG and BMP

Parameters

SessionHandle (in) - the session handle to use
FileName (in) - the name of the file to load

Return values

The DIB handle with the image inside the file, 0 if an error occurred.

3.14 BCR_ImportDDB

C/C++ Declaration

```
__stdcall long BCR_ImportDDB (long SessionHandle,  
HBITAMP BitmapHandle, HPALETTE PaletteHandle);
```

C# Declaration

```
int BCR_ImportDDB (int SessionHandle, int  
BitmapHandle, int PaletteHandle);
```

Visual Basic Declaration

```
Function BCR_ImportDDB(ByVal Session As Integer,  
ByVal BitmapHandle As Integer, ByVal PaletteHandle  
As Integer) As Integer
```

Visual Basic .NET Declaration

```
Function BCR_ImportDDB(ByVal Session As Integer,  
ByVal BitmapHandle As Integer, ByVal PaletteHandle  
As Integer) As Integer
```

Delphi Declaration

```
Function BCR_ImportDDB(Session:Integer,  
BitmapHandle:Integer,  
PaletteHandle:Integer):Integer;stdcall;
```

Java Declaration

```
int BCR_ImportDDB (int SessionHandle,int  
BitmapHandle, int PaletteHandle);
```

Description

This function allows to import a DDB (Device Dependant Bitmap) from file obtaining a DIB handle.

Parameters

SessionHandle (in) - the session handle to use

BitmapHandle (in) - the handle of DDB to import

PaletteHandle (in) - the handle of DDB palette to import. Passing 0 it will be used a standard palette.

Return values

The DIB handle with the image inside, 0 if an error occurred.

3.15 BCR_FreeImage

C/C++ Declaration

```
__stdcall void BCR_FreeImage(long SessionHandle,  
long DIBHandle);
```

C# Declaration

```
void BCR_FreeImage(int SessionHandle, int  
DIBHandle);
```

Visual Basic Declaration

```
Sub BCR_FreeImage(ByVal SessionHandle As Integer,  
ByVal DIBHandle As Integer);
```

Visual Basic .NET Declaration

```
Sub BCR_FreeImage(ByVal SessionHandle As Integer,  
ByVal DIBHandle As Integer);
```

Delphi Declaration

```
Procedure BCR_FreeImage(SessionHandle:Integer,  
DIBHandle:Integer):Integer;stdcall;
```

Java Declaration

```
void BCR_FreeImage(int SessionHandle,int  
DIBHandle);
```

Description

This function allows to remove from memory an image previously loaded from file or imported from DDB.

Parameters

SessionHandle (in) - the session handle to use

CharIndex (in) - the index of the character . First character is 0, last

is the ICR_GetCharactersCount-1.

CharAlternative (in) the index of the alternative, from 0 (hi confidence) to 2 (low confidence).

Left (out) - the buffer where will be moved the left position of the rect containg the character.

Top (out) - the buffer where will be moved the top position of the rect containg the character.

Right (out) - the buffer where will be moved the right position of the rect containg the character.

Bottom (out) - the buffer where will be moved the bottom position of the rect containg the character.

Return values

n/a

3.16 LoadBCRLibrary

C/C++ Declaration

```
RECOBCR_API void LoadBCRLibrary(void)
```

Description

Load the BCR DLL library: you have to use this function one time before to use other API functions from Visual C++.

This function is not required using the API from Delphi or Visual Basic

3.17 FreeBCRLibrary

C/C++ Declaration

```
RECOIO_API void FreeIOLibrary(void)
```

Description

Unload the BCR DLL library: you have to use this function one time before to exit from your Visual C++ application.

This function is not required using the API from Delphi or Visual Basic

Sample

V

4 Sample

4.1 Samples

4.1.1 Visual C++

This sample code performs barcode recognition on image available on clipboard.

```
int RecognizeBarcodesOnClipboard()
{
    // Load dynamically the library
    LoadBCRLibrary();
    // Init the BCR session
    int Session= BCR_Init("demo", "demo");
    long hBitmap;
    char RecognizedString[255];
    // Check if a DIB is available in clipboard
    bool bAvail=IsClipboardFormatAvailable(CF_DIB);
    hBitmap = 0;
    if (bAvail)
    {
        // Open the Clipboard
        ::OpenClipboard(NULL);
        // Retrieve the DIB from clipboard
        hBitmap = (long)
        GetClipboardData(CF_DIB);
        // Recognize barcodes Code39 or 2of5i, 1 per page, from 5 to 15 characters
        // with laser size 3, laser step 32,image quality normal, image orientation
        int nCodes= BCR_RecognizeEx(Session,(long) hBitmap, 32 or 1, 1, 5, 15);
        // Close the Clipboard
        ::CloseClipboard();
        // Check if there are recognized chars
        if (nCodes>0) {
            // Retrieve the first barcode recognized characters
            nChar = BCR_GetCodeText(Session, 0, RecognizedString);
            // Make the buffer a null terminated string
            RecognizedString[nChar]=0;
            // Show the recognized characters
            MessageBox(NULL,
            RecognizedString, "RESULT", MB_OK);
        }
        // Show an error message
        else MessageBox(NULL, "No barcodes recognized !", "ERROR", MB_OK);
    }
    // Show an error message
    else MessageBox(NULL, "Unable to paste DIB","ERROR", MB_OK);
    // Close the session
    BCR_Done(Session);
    // Unload the library
    FreeBCRLibrary();
    return 0;
}
```

4.1.2 Visual Basic

```
This sample code performs barcode recognition on image available on clipboard.

Private RecognizeBarcodesOnClipboard()
' Declare some variables
Dim DIBHandle As Long
Dim CodeStr As String
Dim Codes As Long
Dim Code As Long
Dim Dummy As Long
Dim Orientation As Long
Dim CodeString As String
Dim CodeLen As Long
Dim BCRSession As Long

' open the session
BCRSession = BCR_Init("demo", "demo")
' If there's a DIB on the clipboard, get it
If Clipboard.GetFormat(vbCFDIB) Then
    OpenClipboard (hwnd)
    DIBHandle = GetClipboardData(vbCFDIB)
    ' Try to recognize barcodes
    ' Code39 or 2of5i
    ' max 4 per page
    ' from 3 to 16 characters
    ' virtual laser size 2, virtual laser step 1
    ' normal image quality
    ' orientation left to right or right to left
    ' check digit verification enabled
    Codes = BCR_RecognizeEx(BCRSession, DIBHandle,
        BCR_Code39 Or BCR_Code2of5i, 4, 3, 16, 2, 10,
        BCR_NORMAL_QUALITY, BCR_LeftToRight Or
        BCR_RightToLeft, BCR_CHECKDIGIT_ENABLED)
    ' Check if at least a code was recognized
    If Codes > 0 Then
        For Code = 0 To Codes - 1
            ' retrieve the len of code
            CodeLen = BCR_GetCodeLen(BCRSession, Code)
            ' allocate space for the code in a string
            CodeStr = Space(CodeLen)
            ' retrieve the code data
            Dummy = BCR_GetCodeText(BCRSession, Code, CodeStr)
            Orientation = BCR_GetCodeOrientation(BCRSession, Code)
            ' show the code data
            MsgBox ("Recognized codes " & Str(Code + 1) & " of " & Str(Codes) & " codes")
        Next Code
    Else
        MsgBox ("No code recognized !")
    End If
    CloseClipboard
Else
    MsgBox ("No BMP in clipboard !")
End If
' close the session
BCR_Done (BCRSession)
End Sub
```

4.1.3 Delphi

```

This sample code performs barcode recognition on image available on clipboard
procedure RecognizeBarcodesOnClipboard;
Var DIBHandle:Integer;
    BCRSession:Integer;
    BarCodes:Integer;
    Buffer:PChar;
    BarType:Integer;
    BarOrientation:Integer;
    i:integer;
begin
    // Open the BCR session
    BCRSession:=BCR_Init('demo','demo');
    // Check if an image is in clipboard
    if Clipboard.HasFormat(CF_DIB) then
    begin
        // Open the clipboard
        Clipboard.Open;
        // Retrieve the dib
        DIBHandle:=Clipboard.GetAsHandle(CF_DIB);
        // Recognize the barcode
        // Type: Code39, I2of5
        // Max expected codes: 4
        // Codes length: from 3 to 20 characters
        // Virtual laser step/size: 2/10
        // Image Quality: normal
        // Orientation: LeftToRight or RightToLeft
        // CheckDigit Verification: enabled
        BarCodes:=BCR_RecognizeEx(BCRSession,DIBHandle,BCR_Code39 or BCR_I2of5);
        // Show the number of recognized barcodes
        ShowMessage('Barcodes recognized: '+IntToStr(BarCodes));
        // Retrieve info for each barcode recognized
        for i:=0 to BarCodes-1 do
        begin
            // Create the buffer for the result
            GetMem(Buffer,255);
            // Retrieve the recognized text
            BCR_GetCodeText(BCRSession,i,Buffer);
            // Retrieve the code type
            BarType:=BCR_GetCodeType(BCRSession,i);
            // Retrieve the code orientation
            BarOrientation:=BCR_GetCodeOrientation(BCRSession,i);
            // Show the code index, data and orientation
            ShowMessage('Barcode '+IntToStr(i+1)+' of '+IntToStr(BarCodes));
            // Free the buffer
            FreeMem(Buffer);
        end;
        // Close the clipboard
        Clipboard.Close;
    end else ShowMessage('No image available in clipboard !');
    // Close the BCR session
    BCR_Done(BCRSession);
end;

```

Annotation